AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently amended) An industrial control system, comprising:

a primary aggregation component associated with an industrial controller, the primary aggregation component aggregates one or more selected data items into an aggregated subset of data items, the primary aggregation component defined and installed at the industrial controller by an entity remote from the controller,

a communications component associated with the entity remote from the controller, the communications component transmits the subset of data items via a singular communications packet across a network and adds at least one secondary aggregation component at the industrial controller based upon at least one of increased data demands and network protocol considerations; and

a component associated with the entity remote from the industrial controller, the component receives handle information from the industrial controller relating to the selected data items and employs the handle information <u>as a constant numeric reference</u> to generate an update data packet to update data locations in the industrial controller.

- (Previously Presented) The system of claim 1, the entity is a client application that selects and requests the subset of data items from the controller.
- (Original) The system of claim 2, the client application is at least one of a data logging application and a Human and Machine Interface (HMI) that interacts with the industrial controller.

- 4. (Original) The system of claim 2, further comprising a communications server adapted to interact with the client application, the network and the industrial controller, the industrial controller including a communications driver to interface with the communications server and the network.
- (Previously Presented) The system of claim 1, the communications component sends a data request to the industrial controller relating to the subset of data items.
- 6. (Original) The system of claim 5, the industrial controller sending a response to the request including at least one of tag and value information associated with the tag, the tag and value information relating to the subset of data items.
- (Previously Presented) The system of claim 6, the communications component employing the tag and value information received in the response to build the primary aggregation component on the industrial controller.
- (Cancelled)
- (Previously Presented) The system of claim 1, further comprising removing the one or more secondary aggregation components based upon decreased data demands.
- 10. (Previously Presented) The system of claim 1, further comprising at least one of dynamically increasing and decreasing the amount of selected data items in the primary aggregation component based upon data demands received from the network.
- (Previously Presented) The system of claim 1, the primary aggregation component is an
 object including at least one of class attributes, instance attributes, services and a data buffer.
- 12. (Original) The system of claim 11, the class attributes supply information such as revision level information of the object, an instance number, and a number of instances of an associated class

- 13. (Original) The system of claim 11, the instance attributes include setting for at least one of object update times, event triggers, whether to update the object based on rate, demand and other criteria, where in a data stream triggers are located, whether to continue on an overflow, number of drivers currently installed, timestamp information, size of buffers, start times, and object lifetime settings.
- (Original) The system of claim 11, the services include at least one of Get All Attributes,
 Get All List, Set Attributes List, Reset, Start, Stop, Create Object and Delete Object.
- 15. (Original) The system of claim 11, the data buffer including at least one of 1 to L data items, L being an integer, and includes at least one of the following types: single valued elements, bit, byte, 16 bit, 32 bit, greater than 32 bit configurations, unsigned integers, signed integers, floating point elements, single dimension array, multiple dimension array configurations, and user defined tags (UDT).
- 16. (Original) The system of claim 15, the single valued elements include at least one of a tag identifier and an associated value.
- 17. (Original) The system of claim 15, the single dimension arrays include at least one of an array element ID, a value, a begin array element ID and a length.
- 18. (Previously Presented) The system of claim 1, further comprising removing the primary aggregation component based upon at least one of a loss of communications and a connection timeout.
- (Previously Presented) The system of claim 1, further comprising removing the primary aggregation component based upon an explicit command.
- 20. (Cancelled)

21. (Currently amended) A method to facilitate data communications with an industrial controller, comprising:

requesting tag information from a controller;

building an object from the tag information provided by the controller,

installing the object on the controller;

updating object data on the controller;

adding data items of interest to the object, the data items arranged according to at least one of contiguous and non-contiguous address memory locations; and

receiving data from the object that has been updated by the controller,

receiving handle information from the industrial controller relating to the selected data items; and

employing the handle information <u>as a constant numeric reference</u> to generate an update data packet to update data locations in the industrial controller.

- (Original) The method of claim 21, further comprising interacting with the controller over a network connection.
- (Cancelled)
- 24. (Original) The method of claim 21, further comprising updating the object *via* at least one of a periodic occurrence, an event driven occurrence, and a request.
- (Original) The method of claim 21, further comprising removing the object from the controller when a client no longer requests data items of interest.
- 26. (Original) The method of claim 25, further comprising removing the object based upon at least one of an event and network connections being disrupted for a time period that is greater than a predetermined amount of time that is configured at the controller.
- (Original) The method of claim 21, further comprising placing data items of interest in a scanning list.

- (Original) The method of claim 27, the list indicates which data items are to be periodically updated for a client application.
- (Cancelled)
- (Cancelled)
- (Currently amended) A system to facilitate data communications with an industrial controller, comprising:

means for requesting tag identifiers from a controller;

means for constructing an optimized data packet from the tag identifiers requested from the controller:

means for installing the optimized data packet on the controller;

means for refreshing the optimized data packet on the controller;

means for adding data items of interest to the data packet, the data items arranged according to at least one of contiguous and non-contiguous address memory locations;

means for transmitting data from the optimized data packet that has been refreshed by the controller; and

means for updating the controller via employment of handle information as a constant numeric reference.

- (Cancelled)
- 33. (Previously Presented) An industrial controller, comprising:
 - a first component that processes information received from a remote entity;
- a primary aggregation component that aggregates one or more selected data items into an aggregated subset of data items, the primary aggregation component defined and installed <u>at the</u> industrial controller by an entity remote from the industrial controller;
- a communications component associated with the entity remote from the controller, the communications component transmits the subset of data items via a singular communications packet across a network and adds at least one secondary aggregation component at the industrial

controller based upon at least one of increased data demands and network protocol considerations: and

- a component associated with the entity remote from the industrial controller, the component receives handle information from the industrial controller relating to the selected data items and employs the handle information as a constant numeric reference to generate an update data packet to update data locations in the industrial controller.
- 34. (Original) The controller of claim 33, the first component is a processor adapted to provide access to a variable memory associated with the controller, the variable memory storing the one or more selected data items.
- 35. (Original) The controller of claim 34, the processor interacts with the communications component to aggregate and transmit the subset of data items, the communications component is a communications driver configured for the network.
- (Original) The controller of claim 35, the network is at least one of an Ethernet,
 ControlNet, a DeviceNet, RS-232, RS-422, RS-485.
- (Original) The controller of claim 35, the communications driver adapted to communicate
 with a communications server associated with a client application.
- (Original) The controller of claim 37, the client application is a Human and Machine Interface (HMI).
- (Original) The controller of claim 37, the communications server installs the aggregation component on the industrial controller.